

STS 폴리 표준 치수표 (축 홀가공 타입)

S8M형

S8M0400 (벨트폭 40mm용)




는 재고판매 하고 있습니다.

단위 : mm

잇수	형상	재질	dp	do	W	ℓ	WA	S	B	db	d			폴리에상질량 (kg)		플렌지 품 번
											MAX		MIN			
											A	B, B ₁	A, B, B ₁	A	B, B ₁	
18	A, B	기계구조용탄소강강재	45.84	44.46	50	65	44	3	15	29	28	19	12	0.47	0.53	FS 5333
19	A, B		48.38	47.01	50	65	44	3	15	34	30	22	12	0.54	0.63	FS 5638
20	A, B		50.93	49.56	50	65	44	3	15	35	32	23	12	0.61	0.71	FS 5939
21	A, B		53.48	52.10	50	65	44	3	15	35	34	23	12	0.68	0.78	FS 5939
22	A, B		56.02	54.65	50	65	44	3	15	35	35	23	12	0.76	0.86	FS 6242
24	A, B		61.12	59.74	50	65	44	3	15	40	39	25	12	0.93	1.0	FS 6848
26	A, B		66.21	64.84	50	65	44	3	15	40	42	25	12	1.1	1.2	FS 7555
28	A, B		71.30	69.93	50	65	44	3	15	50	44	30	12	1.3	1.5	FS 7753
30	A, B		76.39	75.02	50	65	44	3	15	50	49	30	12	1.5	1.7	FS 8363
32	A, B		81.49	80.12	50	65	44	3	15	65	51	42	12	1.7	2.1	FS 8969
34	A, B	소강강재	86.58	85.21	50	65	44	3	15	65	55	42	12	2.0	2.4	FS 9272
36	A, B		91.67	90.30	50	65	44	3	15	75	58	45	12	2.2	2.7	FS 9878
40	A, B		101.86	100.49	50	65	44	3	15	80	65	50	12	2.8	3.4	FS 10887
44	A, B		112.05	110.67	50	73	44	3	23	90	72	56	20	3.4	4.5	FS120100
48	A, B		122.23	120.86	50	73	44	3	23	100	78	62	20	4.1	5.5	FS129108
50	A, B		127.32	125.95	50	73	44	3	23	100	82	62	20	4.5	5.8	FS136116
60	A, B		152.79	151.42	50	73	44	3	23	100	107	62	20	6.6	8.0	FS160140
72	B ₁	구상흑연주철	183.35	181.97	54	77	—	—	23	100	—	62	25	—	11.8	—
84	B ₁		213.90	212.53	54	77	—	—	23	115	—	70	25	—	16.2	—
96	B ₁		244.46	243.09	54	77	—	—	23	130	—	80	30	—	21.2	—
120	B ₁		305.58	304.21	54	77	—	—	23	130	—	80	30	—	32.2	—
144	B ₁		366.69	365.32	54	77	—	—	23	130	—	80	30	—	45.7	—
156	B ₁		397.25	395.88	54	77	—	—	23	130	—	80	30	—	53.4	—

S8M0600 (벨트폭 60mm용)



는 재고판매 하고 있습니다.

단위 : mm

잇수	형상	재질	dp	do	W	ℓ	WA	S	B	db	d			폴리에상질량 (kg)		플렌지 품 번
											MAX		MIN			
											A	B, B ₁	A, B, B ₁	A	B, B ₁	
18	A, B	기계구조용탄소강강재	45.84	44.46	71	86	65	3	15	29	28	19	12	0.67	0.73	FS 5333
19	A, B		48.38	47.01	71	86	65	3	15	34	30	22	12	0.77	0.86	FS 5638
20	A, B		50.93	49.56	71	86	65	3	15	35	32	23	12	0.87	0.97	FS 5939
21	A, B		53.48	52.10	71	86	65	3	15	35	34	23	12	0.97	1.0	FS 5939
22	A, B		56.02	54.65	71	86	65	3	15	35	35	23	12	1.0	1.1	FS 6242
24	A, B		61.12	59.74	71	86	65	3	15	40	39	25	12	1.3	1.4	FS 6848
26	A, B		66.21	64.84	71	86	65	3	15	40	42	25	12	1.5	1.7	FS 7555
28	A, B		71.30	69.93	71	86	65	3	15	50	44	30	12	1.8	2.0	FS 7753
30	A, B		76.39	75.02	71	86	65	3	15	50	49	30	12	2.1	2.4	FS 8363
32	A, B		81.49	80.12	71	86	65	3	15	65	51	42	12	2.5	2.8	FS 8969
34	A, B	소강강재	86.58	85.21	71	86	65	3	15	65	55	42	12	2.8	3.2	FS 9272
36	A, B		91.67	90.30	71	86	65	3	15	75	58	45	12	3.2	3.7	FS 9878
40	A, B		101.86	100.49	71	86	65	3	15	80	65	50	12	4.0	4.6	FS 10887
44	A, B		112.05	110.67	71	94	65	3	23	90	72	56	20	4.9	6.1	FS120100
48	A, B		122.23	120.86	71	94	65	3	23	100	78	62	20	5.8	7.2	FS129108
50	A, B		127.32	125.95	71	94	65	3	23	100	82	62	20	6.4	7.7	FS136116
60	A, B		152.79	151.42	71	94	65	3	23	100	107	62	20	9.4	10.7	FS160140
72	B ₁	구상흑연주철	183.35	181.97	75	98	—	—	23	100	—	62	25	—	15.9	—
84	B ₁		213.90	212.53	75	98	—	—	23	115	—	70	25	—	21.8	—
96	B ₁		244.46	243.09	75	98	—	—	23	130	—	80	30	—	28.5	—
120	B ₁		305.58	304.21	75	98	—	—	23	130	—	80	30	—	43.9	—
144	B ₁		366.69	365.32	75	98	—	—	23	130	—	80	30	—	62.6	—
156	B ₁		397.25	395.88	75	98	—	—	23	130	—	80	30	—	73.3	—

d MAX 치수의 키홈 가공의 경우 별도 상담을 해주십시오.