

싱크로 벨트 (고무·폴리우레탄) 표준길이표

XH형

피치 : 22.225mm

호 칭	피치원주 (mm)	잇수	R	u
※ 507XH	1289.05	58	●	—
※ 560XH	1422.40	64	●	—
※ 630XH	1600.20	72	●	—
※ 700XH	1778.00	80	●	—
735XH	1866.90	84	●	—
※ 770XH	1955.80	88	●	—
※ 840XH	2133.60	96	●	—
875XH	2222.50	100	●	—
927XH	2355.85	106	●	—
※ 980XH	2489.20	112	●	—
※ 1120XH	2844.80	128	●	—
※ 1260XH	3200.40	144	●	—
※ 1400XH	3556.00	160	●	—
※ 1540XH	3911.60	176	●	—
※ 1750XH	4445.00	200	●	—

XXH형

피치 : 31.75mm

호 칭	피치원주 (mm)	잇수	R	u
※ 700XXH	1778.00	56	●	—
※ 800XXH	2032.00	64	●	—
※ 900XXH	2286.00	72	●	—
※ 1000XXH	2540.00	80	●	—
※ 1200XXH	3048.00	96	●	—
※ 1400XXH	3556.00	112	●	—
※ 1600XXH	4064.00	128	●	—
※ 1800XXH	4572.00	144	●	—
1915XXH	4857.75	153	●	—

(비고)

※표시는 RMA 규격 사이즈

T2.5형

피치 : 2.5mm

호 칭	피치원주 (mm)	잇수	R	u
T2.5-120	120.0	48	—	●
T2.5-145	145.0	58	—	●
T2.5-160	160.0	64	—	●
T2.5-177.5	177.5	71	—	●
T2.5-200	200.0	80	—	●
T2.5-230	230.0	92	—	●
T2.5-245	245.0	98	—	●
T2.5-265	265.0	106	—	●
T2.5-285	285.0	114	—	●
T2.5-305	305.0	122	—	●
T2.5-317.5	317.5	127	—	●
T2.5-330	330.0	132	—	●
T2.5-380	380.0	152	—	●
T2.5-420	420.0	168	—	●
T2.5-480	480.0	192	—	●
T2.5-492.5	492.5	197	—	●
T2.5-500	500.0	200	—	●
T2.5-600	600.0	240	—	●
T2.5-620	620.0	248	—	●
T2.5-650	650.0	260	—	●
T2.5-780	780.0	312	—	●
T2.5-915	915.0	366	—	●
T2.5-950	950.0	380	—	●

폴리우레탄 싱크로 벨트 표준길이표

T5형

피치 : 5.0mm

호 칭	피치원주 (mm)	잇수	R	u
T5-165	165.0	33	—	●
T5-185	185.0	37	—	●
T5-200	200.0	40	—	●
T5-215	215.0	43	—	●
T5-220	220.0	44	—	●
T5-225	225.0	45	—	●
T5-245	245.0	49	—	●
T5-250	250.0	50	—	●
T5-255	255.0	51	—	●
T5-260	260.0	52	—	●
T5-270	270.0	54	—	●
T5-275	275.0	55	—	●
T5-280	280.0	56	—	●
T5-295	295.0	59	—	●
T5-300	300.0	60	—	●
T5-305	305.0	61	—	●
T5-325	325.0	65	—	●
T5-330	330.0	66	—	●
T5-340	340.0	68	—	●
T5-350	350.0	70	—	●
T5-355	355.0	71	—	●
T5-365	365.0	73	—	●
T5-375	375.0	75	—	●
T5-390	390.0	78	—	●
T5-400	400.0	80	—	●
T5-410	410.0	82	—	●
T5-420	420.0	84	—	●
T5-425	425.0	85	—	●
T5-450	450.0	90	—	●
T5-455	455.0	91	—	●
T5-465	465.0	93	—	●
T5-475	475.0	95	—	●
T5-480	480.0	96	—	●
T5-500	500.0	100	—	●
T5-510	510.0	102	—	●
T5-525	525.0	105	—	●
T5-545	545.0	109	—	●
T5-550	550.0	110	—	●
T5-560	560.0	112	—	●
T5-575	575.0	115	—	●
T5-600	600.0	120	—	●
T5-610	610.0	122	—	●
T5-620	620.0	124	—	●
T5-630	630.0	126	—	●
T5-640	640.0	128	—	●
T5-650	650.0	130	—	●
T5-660	660.0	132	—	●
T5-675	675.0	135	—	●
T5-690	690.0	138	—	●
T5-695	695.0	139	—	●
T5-700	700.0	140	—	●
T5-720	720.0	144	—	●
T5-750	750.0	150	—	●
T5-780	780.0	156	—	●
T5-800	800.0	160	—	●
T5-815	815.0	163	—	●
T5-840	840.0	168	—	●
T5-850	850.0	170	—	●
T5-900	900.0	180	—	●
T5-940	940.0	188	—	●
T5-990	990.0	198	—	●
T5-1000	1000.0	200	—	●
T5-1075	1075.0	215	—	●
T5-1100	1100.0	220	—	●
T5-1140	1140.0	228	—	●
T5-1215	1215.0	243	—	●
T5-1380	1380.0	276	—	●
T5-1440	1440.0	288	—	●

T10형

피치 : 10.0mm

호 칭	피치원주 (mm)	잇수	R	u
T10-260	260.0	26	—	●
T10-370	370.0	37	—	●
T10-400	400.0	40	—	●
T10-410	410.0	41	—	●
T10-440	440.0	44	—	●
T10-450	450.0	45	—	●
T10-500	500.0	50	—	●
T10-530	530.0	53	—	●
T10-560	560.0	56	—	●
T10-610	610.0	61	—	●
T10-630	630.0	63	—	●
T10-660	660.0	66	—	●
T10-690	690.0	69	—	●
T10-700	700.0	70	—	●
T10-720	720.0	72	—	●
T10-750	750.0	75	—	●
T10-780	780.0	78	—	●
T10-810	810.0	81	—	●
T10-840	840.0	84	—	●
T10-880	880.0	88	—	●
T10-890	890.0	89	—	●
T10-900	900.0	90	—	●
T10-920	920.0	92	—	●
T10-960	960.0	96	—	●
T10-970	970.0	97	—	●
T10-980	980.0	98	—	●
T10-1000	1000.0	100	—	●
T10-1010	1010.0	101	—	●
T10-1080	1080.0	108	—	●
T10-1100	1100.0	110	—	●
T10-1110	1110.0	111	—	●
T10-1140	1140.0	114	—	●
T10-1150	1150.0	115	—	●
T10-1210	1210.0	121	—	●
T10-1240	1240.0	124	—	●
T10-1250	1250.0	125	—	●
T10-1300	1300.0	130	—	●
T10-1320	1320.0	132	—	●
T10-1350	1350.0	135	—	●
T10-1390	1390.0	139	—	●
T10-1400	1400.0	140	—	●
T10-1420	1420.0	142	—	●
T10-1440	1440.0	144	—	●
T10-1450	1450.0	145	—	●
T10-1460	1460.0	146	—	●
T10-1500	1500.0	150	—	●
T10-1560	1560.0	156	—	●
T10-1610	1610.0	161	—	●
T10-1750	1750.0	175	—	●
T10-1780	1780.0	178	—	●
T10-1880	1880.0	188	—	●
T10-1960	1960.0	196	—	●
T10-2250	2250.0	225	—	●