

TN10형 기준전동용량표 (6mm폭당)

단위 : W

소PULLEY잇수		34	36	40	44	48	52	56	60
피치원직경 (mm)		10.82	11.46	12.73	14.01	15.28	16.55	17.83	19.10
소 풀 리 회 전 수 (rpm)	950	3.0	3.2	3.5	3.9	4.2	4.6	5.0	5.3
	1160	3.7	3.9	4.3	4.8	5.2	5.6	6.0	6.5
	1425	4.5	4.8	5.3	5.8	6.4	6.9	7.4	8.0
	1750	5.5	5.9	6.5	7.2	7.8	8.5	9.1	9.8
	2850	9.0	9.5	10.6	11.6	12.7	13.7	14.8	15.8
	3450		11.5	12.8	14.1	15.3	16.6	17.8	19.1
	100	0.3	0.3	0.4	0.4	0.4	0.5	0.5	0.6
	200	0.6	0.7	0.7	0.8	0.9	1.0	1.0	1.1
	300	1.0	1.0	1.1	1.2	1.3	1.5	1.6	1.7
	400	1.3	1.3	1.5	1.6	1.8	1.9	2.1	2.2
	500	1.6	1.7	1.9	2.0	2.2	2.4	2.6	2.8
	600	1.9	2.0	2.2	2.5	2.7	2.9	3.1	3.4
	700	2.2	2.3	2.6	2.9	3.1	3.4	3.7	3.9
	800	2.5	2.7	3.0	3.3	3.6	3.9	4.2	4.5
	900	2.9	3.0	3.4	3.7	4.0	4.4	4.7	5.0
	1000	3.2	3.4	3.7	4.1	4.5	4.8	5.2	5.6
	1100	3.5	3.7	4.1	4.5	4.9	5.3	5.7	6.1
	1200	3.8	4.0	4.5	4.9	5.4	5.8	6.3	6.7
	1300	4.1	4.4	4.8	5.3	5.8	6.3	6.8	7.3
	1400	4.4	4.7	5.2	5.7	6.3	6.8	7.3	7.8
	1500	4.7	5.0	5.6	6.1	6.7	7.3	7.8	8.4
	1600	5.1	5.4	6.0	6.6	7.1	7.7	8.3	8.9
	1700	5.4	5.7	6.3	7.0	7.6	8.2	8.9	9.5
	1800	5.7	6.0	6.7	7.4	8.0	8.7	9.4	10.0
	1900	6.0	6.4	7.1	7.8	8.5	9.2	9.9	10.6
	2000	6.3	6.7	7.4	8.2	8.9	9.7	10.4	11.1
	2100	6.6	7.0	7.8	8.6	9.4	10.1	10.9	11.7
	2200	7.0	7.4	8.2	9.0	9.8	10.6	11.4	12.2
	2300	7.3	7.7	8.6	9.4	10.3	11.1	12.0	12.8
	2400	7.6	8.0	8.9	9.8	10.7	11.6	12.5	13.3
	2500	7.9	8.4	9.3	10.2	11.1	12.1	13.0	13.9
	2600	8.2	8.7	9.7	10.6	11.6	12.5	13.5	14.4
	2700	8.5	9.0	10.0	11.0	12.0	13.0	14.0	15.0
	2800	8.9	9.4	10.4	11.4	12.5	13.5	14.5	15.5
	2900	9.2	9.7	10.8	11.8	12.9	14.0	15.0	16.1
	3000	9.5	10.0	11.1	12.2	13.3	14.4	15.5	16.6
	3200		10.7	11.9	13.1	14.2	15.4	16.6	17.7
	3400		11.4	12.6	13.9	15.1	16.3	17.6	18.8
	3600		12.0	13.3	14.7	16.0	17.3	18.6	19.9
	3800		12.7	14.1	15.5	16.9	18.2	19.6	21.0
	4000		13.3	14.8	16.3	17.7	19.2	20.6	22.1
	4200		14.0	15.5	17.1	18.6	20.1	21.6	23.1
	4400		14.7	16.3	17.9	19.5	21.1	22.6	24.2
	4600		15.3	17.0	18.7	20.3	22.0	23.6	25.2
	4800		16.0	17.7	19.5	21.2	22.9	24.6	26.3
	5000		16.6	18.5	20.3	22.1	23.8	25.6	27.3
	5500		18.3	20.3	22.2	24.2	26.1	28.0	29.9
	6000		19.9	22.1	24.2	26.3	28.4	30.5	32.5