

T5 · DT5형 기준전동용량표 (10mm 폭당)

단위 : W

소PULLEY잇수		12	14	15	16	18	19	20	22	24	26
피치원직경 (mm)		19.10	22.28	23.87	25.46	28.65	30.24	31.83	35.01	38.20	41.38
소 폴 리 회 전 수 (rpm)	950	84	98	105	112	126	133	140	154	168	182
	1160	99	116	124	132	149	157	165	182	199	215
	1425	117	137	146	156	176	185	195	215	234	254
	1750	137	160	171	183	206	217	228	251	274	297
	2850	194	227	243	259	292	308	324	357	389	421
	3450	221	258	276	295	332	350	369	405	442	479
	100	14	17	18	19	21	23	24	26	29	31
	200	21	25	27	28	32	34	35	39	43	46
	300	30	35	37	40	45	47	50	55	60	65
	400	39	45	49	52	58	62	65	71	78	84
	500	48	56	60	64	72	76	80	88	95	103
	600	56	66	70	75	84	89	94	103	113	122
	700	65	75	81	86	97	102	108	119	129	140
	800	73	85	91	97	109	115	121	133	145	157
	900	80	94	100	107	121	127	134	147	161	174
	1000	88	102	110	117	132	139	146	161	176	190
	1100	95	111	119	127	143	151	158	174	190	206
	1200	102	119	128	136	153	162	170	187	204	221
	1300	109	127	136	145	163	172	181	200	218	236
	1400	115	135	144	154	173	183	192	212	231	250
	1500	122	142	152	162	183	193	203	223	244	264
	1600	128	149	160	171	192	203	213	235	256	277
	1700	134	156	168	179	201	212	223	246	268	290
	1800	140	163	175	187	210	222	233	257	280	303
	1900	146	170	182	194	219	231	243	267	291	316
	2000	151	177	189	202	227	240	252	277	303	328
	2100	157	183	196	209	235	248	261	287	314	340
	2200	162	189	203	216	243	257	270	297	324	351
	2300	167	195	209	223	251	265	279	307	335	363
	2400	173	201	216	230	259	273	288	316	345	374
	2500	178	207	222	237	266	281	296	326	355	385
	2600	183	213	228	243	274	289	304	335	365	395
	2700	187	219	234	250	281	297	312	344	375	406
	2800	192	224	240	256	288	304	320	352	384	416
	2900	197	230	246	262	295	312	328	361	394	426
	3000	201	235	252	269	302	319	336	369	403	436
	3200	210	245	263	280	316	333	351	386	421	456
	3400	219	256	274	292	329	347	365	402	438	475
	3600	227	265	284	303	341	360	379	417	455	493
	3800	236	275	294	314	353	373	393	432	471	510
	4000	244	284	304	325	365	386	406	446	487	528
	4200	251	293	314	335	377	398	419	461	502	544
	4400	259	302	323	345	388	410	431	474	518	561
	4600	266	310	333	355	399	421	443	488	532	577
	4800	273	319	342	364	410	433	455	501	546	592
	5000	280	327	350	374	420	444	467	514	560	607
	5500				396	446	470	495	545	594	644
	6000				417	469	496	522	574	626	678
	6500				438	492	520	547	602	656	711
	7000				457	514	543	571	628	685	742
	7500				475	535	565	594	654	713	773
	8000					555	586	617	678	740	802
	8500					574	606	638	702	766	829
	9000					593	626	659	725	790	856
	9500					613	645	679	747	814	882
	10000					628	663	698	768	838	907

표시 범위에서의 사용은 벨트 수명이 단축됩니다.