

TL 싱크로 폴리 표준 치수표 (부싱 타입)

L075 (BELT폭 19.0mm용)

는 재고판매 하고 있습니다.

단위 : mm

| 잇수 | dp | do | 형상 | PULLEY 재질 | TL BUSH | | W | WA | S | db | ℓ | S ₁ | S ₂ | S ₃ | H | PULLEY 예상질량 (kg) | 플랜지 품번 |
|----|--------|--------|-------|--------------|---------|------|----|----|-----|-----|----|----------------|----------------|----------------|----|------------------------|---------|
| | | | | | 형번 | 최대축홀 | | | | | | | | | | | |
| 19 | 57.61 | 56.84 | 4-1BF | 기계구조용탄소강강재 | 3622 | 22 | 26 | 21 | 2.5 | - | 22 | - | 4 | - | - | 0.3 | F 6751 |
| 20 | 60.64 | 59.88 | 4-1BF | | 3622 | 22 | 26 | 21 | 2.5 | - | 22 | - | 4 | - | - | 0.35 | F 6751 |
| 21 | 63.67 | 62.91 | 4-1BF | | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 0.36 | F 7056 |
| 22 | 66.70 | 65.94 | 4-1BF | | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 0.43 | F 7761 |
| 23 | 69.73 | 68.97 | 4-1BF | | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 0.49 | F 7761 |
| 24 | 72.77 | 72.00 | 4-1BF | | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 0.56 | F 8366 |
| 25 | 75.80 | 75.04 | 4-1BF | | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 0.62 | F 8366 |
| 26 | 78.83 | 78.07 | 4-1BF | | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 0.7 | F 8871 |
| 28 | 84.89 | 84.13 | 4-1BF | | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 0.86 | F 9575 |
| 30 | 90.96 | 90.20 | 4-1BF | | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 1.0 | F 9980 |
| 32 | 97.02 | 96.26 | 4-1BF | 회주철 | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 1.2 | F 10385 |
| 34 | 103.08 | 102.32 | 4-1BF | | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 1.4 | F 11595 |
| 36 | 109.15 | 108.39 | 4-1BF | | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 1.6 | F119100 |
| 40 | 121.28 | 120.51 | 4-1BF | | 4225 | 28 | 26 | 21 | 2.5 | - | 25 | - | 1 | - | - | 1.9 | F131110 |
| 42 | 127.34 | 126.58 | 1-1AF | | 5035 | 32 | 26 | 21 | 2.5 | 80 | 35 | 9 | - | - | - | 2.2 | F135115 |
| 44 | 133.40 | 132.64 | 1-1AF | | 5035 | 32 | 26 | 21 | 2.5 | 80 | 35 | 9 | - | - | - | 2.5 | F140120 |
| 48 | 145.53 | 144.77 | 1-1AF | | 5035 | 32 | 26 | 21 | 2.5 | 80 | 35 | 9 | - | - | - | 3.0 | F152130 |
| 50 | 151.60 | 150.83 | 1-1AF | | 5035 | 32 | 26 | 21 | 2.5 | 80 | 35 | 9 | - | - | - | 3.2 | F160140 |
| 60 | 181.90 | 181.15 | 1-2 | | 5035 | 32 | 26 | - | - | 80 | 35 | 9 | - | - | 11 | 2.5 | - |
| 72 | 218.30 | 217.53 | 1-2 | | 6340 | 42 | 26 | - | - | 100 | 40 | 14 | - | - | 11 | 3.5 | - |
| 84 | 254.68 | 253.92 | 1-2 | | 6340 | 42 | 26 | - | - | 100 | 40 | 14 | - | - | 11 | 4.1 | - |

L100 (BELT폭 25.4mm용)

는 재고판매 하고 있습니다.

단위 : mm

| 잇수 | dp | do | 형상 | PULLEY 재질 | TL BUSH | | W | WA | S | db | ℓ | S ₁ | S ₂ | S ₃ | H | PULLEY 예상질량 (kg) | 플랜지 품번 |
|----|--------|--------|-------|--------------|---------|------|----|----|-----|-----|----|----------------|----------------|----------------|----|------------------------|---------|
| | | | | | 형번 | 최대축홀 | | | | | | | | | | | |
| 19 | 57.61 | 56.84 | 4-1BF | 기계구조용탄소강강재 | 3622 | 22 | 32 | 27 | 2.5 | - | 22 | - | 10 | - | - | 0.37 | F 6751 |
| 20 | 60.64 | 59.88 | 4-1BF | | 3622 | 22 | 32 | 27 | 2.5 | - | 22 | - | 10 | - | - | 0.43 | F 6751 |
| 21 | 63.67 | 62.91 | 4-1BF | | 4225 | 28 | 32 | 27 | 2.5 | - | 25 | - | 7 | - | - | 0.44 | F 7056 |
| 22 | 66.70 | 65.94 | 4-1BF | | 4225 | 28 | 32 | 27 | 2.5 | - | 25 | - | 7 | - | - | 0.52 | F 7761 |
| 23 | 69.73 | 68.97 | 4-1BF | | 4225 | 28 | 32 | 27 | 2.5 | - | 25 | - | 7 | - | - | 0.59 | F 7761 |
| 24 | 72.77 | 72.00 | 4-1BF | | 4225 | 28 | 32 | 27 | 2.5 | - | 25 | - | 7 | - | - | 0.68 | F 8366 |
| 25 | 75.80 | 75.04 | 4-1BF | | 4225 | 28 | 32 | 27 | 2.5 | - | 25 | - | 7 | - | - | 0.76 | F 8366 |
| 26 | 78.83 | 78.07 | 4-1BF | | 4225 | 28 | 32 | 27 | 2.5 | - | 25 | - | 7 | - | - | 0.86 | F 8871 |
| 28 | 84.89 | 84.13 | 4-1BF | | 4225 | 28 | 32 | 27 | 2.5 | - | 25 | - | 7 | - | - | 1.1 | F 9575 |
| 30 | 90.96 | 90.20 | 4-1BF | | 4225 | 28 | 32 | 27 | 2.5 | - | 25 | - | 7 | - | - | 1.3 | F 9980 |
| 32 | 97.02 | 96.26 | 4-1BF | 회주철 | 4225 | 28 | 32 | 27 | 2.5 | - | 25 | - | 7 | - | - | 1.5 | F 10385 |
| 34 | 103.08 | 102.32 | 1-1BF | | 5035 | 32 | 32 | 27 | 2.5 | 80 | 35 | 3 | - | - | - | 1.7 | F 11595 |
| 36 | 109.15 | 108.39 | 1-1BF | | 5035 | 32 | 32 | 27 | 2.5 | 80 | 35 | 3 | - | - | - | 1.9 | F119100 |
| 40 | 121.28 | 120.51 | 1-1BF | | 5035 | 32 | 32 | 27 | 2.5 | 80 | 35 | 3 | - | - | - | 2.3 | F131110 |
| 42 | 127.34 | 126.58 | 1-1BF | | 5035 | 32 | 32 | 27 | 2.5 | 80 | 35 | 3 | - | - | - | 2.6 | F135115 |
| 44 | 133.40 | 132.64 | 1-1BF | | 5035 | 32 | 32 | 27 | 2.5 | 80 | 35 | 3 | - | - | - | 2.8 | F140120 |
| 48 | 145.53 | 144.77 | 1-1BF | | 5035 | 32 | 32 | 27 | 2.5 | 80 | 35 | 3 | - | - | - | 3.5 | F152130 |
| 50 | 151.60 | 150.83 | 1-1BF | | 5035 | 32 | 32 | 27 | 2.5 | 80 | 35 | 3 | - | - | - | 3.8 | F160140 |
| 60 | 181.90 | 181.15 | 1-2 | | 6340 | 42 | 32 | - | - | 100 | 40 | 8 | - | - | 11 | 3.5 | - |
| 72 | 218.30 | 217.53 | 1-2 | | 6340 | 42 | 32 | - | - | 100 | 40 | 8 | - | - | 11 | 3.9 | - |
| 84 | 254.68 | 253.92 | 1-2 | | 6340 | 42 | 32 | - | - | 100 | 40 | 8 | - | - | 11 | 4.5 | - |