

TL 싱크로 폴리 표준 치수표 (축홀가공 타입)

XH400 (벨트폭 : 101.6mm용)

비재고품

단위 : mm

| 잇수 | 형상 | 재질 | dp | do | W | ℓ | B | db | d | | K | E | 폴리 예상 질량 (kg) |
|-----|----|------------|--------|--------|-----|-----|----|-----|-----|-----|-----|----|------------------|
| | | | | | | | | | MAX | MIN | | | |
| 18 | A | 기계구조용탄소강강재 | 127.34 | 124.55 | 123 | — | — | — | 60 | 25 | — | — | 9.4 |
| 20 | A | | 141.49 | 138.69 | 123 | — | — | — | 60 | 25 | — | — | 12.0 |
| 22 | A | | 155.64 | 152.84 | 123 | — | — | — | 70 | 25 | — | — | 14.8 |
| 24 | A | | 169.79 | 166.99 | 123 | — | — | — | 80 | 25 | — | — | 17.9 |
| 26 | A | | 183.94 | 181.14 | 123 | — | — | — | 100 | 30 | — | — | 21.0 |
| 28 | A | | 198.08 | 195.29 | 123 | — | — | — | 110 | 30 | — | — | 24.7 |
| 30 | A | | 212.23 | 209.44 | 123 | — | — | — | 120 | 30 | — | — | 28.6 |
| 32 | D | | 226.38 | 223.59 | 123 | 157 | 34 | 110 | 65 | 35 | 172 | 45 | 28.2 |
| 36 | D | | 254.68 | 251.89 | 123 | 157 | 34 | 116 | 70 | 35 | 200 | 45 | 33.5 |
| 40 | D | | 282.98 | 280.18 | 123 | 157 | 34 | 116 | 70 | 35 | 228 | 45 | 38 |
| 44 | D | | 311.28 | 308.48 | 123 | 157 | 34 | 125 | 75 | 35 | 256 | 44 | 45.3 |
| 48 | D | | 339.57 | 336.78 | 123 | 157 | 34 | 130 | 80 | 40 | 284 | 44 | 51.3 |
| 60 | E | | 424.47 | 421.67 | 123 | 157 | 34 | 135 | 85 | 40 | 370 | 44 | 64.8 |
| 72 | E | | 509.36 | 506.57 | 123 | 157 | 34 | 145 | 95 | 40 | 454 | 42 | 86.7 |
| 84 | E | | 594.25 | 591.46 | 123 | 157 | 34 | 152 | 100 | 45 | 538 | 42 | 109 |
| 96 | E | | 679.15 | 676.35 | 123 | 157 | 34 | 160 | 105 | 45 | 624 | 42 | 129.3 |
| 120 | E | | 848.93 | 846.14 | 123 | 157 | 34 | 170 | 115 | 45 | 790 | 42 | 191.6 |