

# STS 벨트표준길이

R : 고무 STS  
U : 폴리우레탄 STS

## S1.5M형

벨트호칭	피치원길이 (mm)	잇수	제 조 여 부	
			R	U
S1.5M 92	91.50	61	●	—
93	93.00	62	●	—
95	94.50	63	●	—
98	97.50	65	●	—
99	99.00	66	●	—
101	100.50	67	●	—
102	102.00	68	●	—
108	108.00	72	●	—
119	118.50	79	●	—
134	133.50	89	●	—
150	150.00	100	●	—
158	157.50	105	●	—
161	160.50	107	●	—
164	163.50	109	●	—
165	165.00	110	●	—
168	168.00	112	●	—
174	174.00	116	●	—
180	180.00	120	●	—
185	184.50	123	●	—
186	186.00	124	●	—
204	204.00	136	●	—
206	205.50	137	●	—
210	210.00	140	●	—
224	223.50	149	●	—
225	225.00	150	●	—
236	235.50	157	●	—
240	240.00	160	●	—
255	255.00	170	●	—
261	261.00	174	●	—
263	262.50	175	●	—
273	273.00	182	●	—
281	280.50	187	●	—
288	288.00	192	●	—
290	289.50	193	●	—
303	303.00	202	●	—
305	304.50	203	●	—
315	315.00	210	●	—
335	334.50	223	●	—
390	390.00	260	●	—
441	441.00	294	●	—
444	444.00	296	●	—
480	480.00	320	●	—
1116	1116.00	744	●	—

## S2M형

벨트호칭	피치원길이 (mm)	잇수	제 조 여 부	
			R	U
S2M 74	74.0	37	●	—
76	76.0	38	●	●
78	78.0	39	●	●
80	80.0	40	●	●
84	84.0	42	●	—
86	86.0	43	●	●
88	88.0	44	●	—
90	90.0	45	●	●
92	92.0	46	●	—
94	94.0	47	●	●
96	96.0	48	●	—
98	98.0	49	●	—
100	100.0	50	●	●
102	102.0	51	●	●
104	104.0	52	●	—
106	106.0	53	—	●
108	108.0	54	●	—
110	110.0	55	—	●
112	112.0	56	●	●
114	114.0	57	●	●
116	116.0	58	●	●
118	118.0	59	●	—
120	120.0	60	●	●
122	122.0	61	●	●
124	124.0	62	●	—
126	126.0	63	●	●

## S2M형

벨트호칭	피치원길이 (mm)	잇수	제 조 여 부	
			R	U
S2M128	128.0	64	●	●
130	130.0	65	●	—
132	132.0	66	●	—
134	134.0	67	●	—
136	136.0	68	●	—
138	138.0	69	●	●
140	140.0	70	●	●
142	142.0	71	●	●
144	144.0	72	●	●
146	146.0	73	●	—
148	148.0	74	●	●
150	150.0	75	●	—
152	152.0	76	●	—
156	156.0	78	●	—
158	158.0	79	●	●
160	160.0	80	●	●
162	162.0	81	●	—
164	164.0	82	●	●
166	166.0	83	●	●
168	168.0	84	●	●
170	170.0	85	●	●
172	172.0	86	●	●
174	174.0	87	●	—
176	176.0	88	●	●
178	178.0	89	●	—
180	180.0	90	●	●
182	182.0	91	●	—
184	184.0	92	●	●
186	186.0	93	●	●
188	188.0	94	●	—
190	190.0	95	●	●
192	192.0	96	●	—
194	194.0	97	●	—
196	196.0	98	●	—
198	198.0	99	●	—
200	200.0	100	●	●
202	202.0	101	●	—
204	204.0	102	●	—
206	206.0	103	●	●
208	208.0	104	●	—
210	210.0	105	●	—
212	212.0	106	●	—
214	214.0	107	●	●
216	216.0	108	●	●
218	218.0	109	●	●
220	220.0	110	●	●
222	222.0	111	●	—
224	224.0	112	●	●
226	226.0	113	●	—
230	230.0	115	●	●
232	232.0	116	●	—
234	234.0	117	●	●
236	236.0	118	●	●
238	238.0	119	●	●
240	240.0	120	●	●
242	242.0	121	●	—
244	244.0	122	●	—
248	248.0	124	●	—
250	250.0	125	●	●
252	252.0	126	●	—
254	254.0	127	●	—
256	256.0	128	●	●
258	258.0	129	●	●
260	260.0	130	●	●
262	262.0	131	●	—
264	264.0	132	●	●
266	266.0	133	●	●
268	268.0	134	●	—
270	270.0	135	●	—
272	272.0	136	●	—
274	274.0	137	●	—
276	276.0	138	●	—

## S2M형

벨트호칭	피치원길이 (mm)	잇수	제 조 여 부	
			R	U
S2M278	278.0	139	●	—
280	280.0	140	●	—
282	282.0	141	●	—
284	284.0	142	●	—
286	286.0	143	●	—
288	288.0	144	●	—
290	290.0	145	●	●
292	292.0	146	●	—
294	294.0	147	●	—
296	296.0	148	●	●
300	300.0	150	●	●
304	304.0	152	●	—
306	306.0	153	●	—
308	308.0	154	●	—
310	310.0	155	●	—
312	312.0	156	●	—
314	314.0	157	●	●
316	316.0	158	●	●
318	318.0	159	●	—
320	320.0	160	●	●
322	322.0	161	●	—
324	324.0	162	●	—
326	326.0	163	●	—
328	328.0	164	●	—
330	330.0	165	●	—
332	332.0	166	●	—
334	334.0	167	●	●
336	336.0	168	●	—
338	338.0	169	●	—
340	340.0	170	●	●
342	342.0	171	●	—
344	344.0	172	●	—
350	350.0	175	●	—
354	354.0	177	●	●
360	360.0	180	●	●
364	364.0	182	●	—
370	370.0	185	●	—
372	372.0	186	●	—
374	374.0	187	●	—
376	376.0	188	●	—
380	380.0	190	●	●
386	386.0	193	●	—
390	390.0	195	●	—
396	396.0	198	●	●
400	400.0	200	●	●
406	406.0	203	●	—
408	408.0	204	●	—
410	410.0	205	●	—
416	416.0	208	●	—
420	420.0	210	●	—
426	426.0	213	●	—
428	428.0	214	●	—
434	434.0	217	●	—
436	436.0	218	●	●
438	438.0	219	●	—
440	440.0	220	●	●
448	448.0	224	●	●
452	452.0	226	●	—
454	454.0	227	●	●
456	456.0	228	●	—
460	460.0	230	●	●
468	468.0	234	●	—
474	474.0	237	●	●
480	480.0	240	●	●
486	486.0	243	●	—
488	488.0	244	—	●
490	490.0	245	●	—
494	494.0	247	●	●
500	500.0	250	●	●
504	504.0	252	—	●
506	506.0	253	●	—
520	520.0	260	●	●
530	530.0	265	●	—
532	532.0	266	●	—
540	540.0	270	●	—