

S2M형

벨트호칭	피치원길이 (mm)	잇수	제 조 여 부	
			R	U
S2M544	544.0	272	—	●
548	548.0	274	—	●
550	550.0	275	●	—
558	558.0	279	●	—
560	560.0	280	●	●
572	572.0	286	●	—
580	580.0	290	●	●
594	594.0	297	●	—
596	596.0	298	●	—
600	600.0	300	●	●
604	604.0	302	●	—
606	606.0	303	●	—
620	620.0	310	●	●
630	630.0	315	●	●
632	632.0	316	●	—
650	650.0	325	●	—
652	652.0	326	●	—
654	654.0	327	●	●
656	656.0	328	●	—
660	660.0	330	●	—
668	668.0	334	●	—
676	676.0	338	●	—
692	692.0	346	●	—
700	700.0	350	●	—
710	710.0	355	●	●
726	726.0	363	●	—
742	742.0	371	●	—
752	752.0	376	●	—
754	754.0	377	●	●
766	766.0	383	●	—
790	790.0	395	—	●
796	796.0	398	●	—
800	800.0	400	●	●
806	806.0	403	—	●
810	810.0	405	●	—
826	826.0	413	●	—
828	828.0	414	—	●
848	848.0	424	●	—
856	856.0	428	●	—
864	864.0	432	●	—
898	898.0	449	●	—
900	900.0	450	●	※●
940	940.0	470	●	—
946	946.0	473	●	—
950	950.0	475	●	—
976	976.0	488	—	●
984	984.0	492	●	—
1000	1000.0	500	●	※●
1020	1020.0	510	●	—
1024	1024.0	512	●	—
1032	1032.0	516	●	—
1036	1036.0	518	●	—
1042	1042.0	521	●	—
1064	1064.0	532	●	—
1066	1066.0	533	●	—
1074	1074.0	537	●	—
1086	1086.0	543	●	—
1094	1094.0	547	●	—
1100	1100.0	550	●	—
1110	1110.0	555	●	—
1136	1136.0	568	●	—
1154	1154.0	577	●	—
1166	1166.0	583	●	—
1224	1224.0	612	●	—
1228	1228.0	614	●	—

※표시 사이즈의 폴리우레탄 STS S2M은 아라미드 코드로만 대응 가능합니다.

S3M형

벨트호칭	피치원길이 (mm)	잇수	제 조 여 부	
			R	U
S3M 93	93.0	31	●	—
99	99.0	33	●	—
108	108.0	36	●	—

S3M형

벨트호칭	피치원길이 (mm)	잇수	제 조 여 부	
			R	U
S3M 120	120.0	40	●	●
123	123.0	41	●	—
129	129.0	43	●	—
132	132.0	44	●	—
141	141.0	47	●	—
144	144.0	48	●	●
147	147.0	49	●	—
150	150.0	50	●	●
156	156.0	53	●	—
159	159.0	52	●	●
162	162.0	54	●	●
168	168.0	56	●	—
171	171.0	57	●	●
174	174.0	58	●	●
177	177.0	59	●	●
180	180.0	60	●	—
183	183.0	61	●	—
186	186.0	62	●	●
189	189.0	63	●	—
192	192.0	64	●	●
195	195.0	65	●	●
198	198.0	66	●	—
201	201.0	67	●	●
204	204.0	68	●	●
207	207.0	69	●	—
210	210.0	70	●	●
213	213.0	71	●	●
219	219.0	73	●	●
222	222.0	74	●	●
225	225.0	75	●	●
228	228.0	76	●	—
234	234.0	78	●	—
237	237.0	79	●	●
240	240.0	80	●	●
243	243.0	81	●	—
246	246.0	82	●	●
249	249.0	83	●	—
252	252.0	84	●	●
255	255.0	85	●	●
258	258.0	86	●	—
264	264.0	88	●	●
267	267.0	89	●	—
270	270.0	90	●	●
273	273.0	91	●	—
276	276.0	92	●	●
279	279.0	93	●	—
282	282.0	94	●	—
285	285.0	95	●	●
288	288.0	96	●	—
291	291.0	97	●	—
294	294.0	98	●	—
297	297.0	99	●	—
300	300.0	100	●	●
303	303.0	101	●	—
306	306.0	102	●	—
309	309.0	103	●	—
312	312.0	104	●	●
315	315.0	105	●	—
318	318.0	106	●	●
324	324.0	108	●	—
327	327.0	109	●	●
330	330.0	110	●	—
333	333.0	111	●	—
336	336.0	112	●	—
339	339.0	113	●	●
342	342.0	114	●	●
351	351.0	117	●	—
354	354.0	118	●	●
360	360.0	120	●	●
363	363.0	121	●	—
366	366.0	122	●	—
369	369.0	123	●	—
372	372.0	124	●	—
375	375.0	125	●	—
378	378.0	126	●	●

S3M형

벨트호칭	피치원길이 (mm)	잇수	제 조 여 부	
			R	U
S3M 384	384.0	128	●	—
387	387.0	129	●	—
390	390.0	130	●	●
396	396.0	132	●	—
399	399.0	133	●	—
402	402.0	134	●	—
405	405.0	135	●	●
408	408.0	136	●	—
417	417.0	139	●	—
420	420.0	140	●	—
423	423.0	141	●	—
426	426.0	142	●	—
432	432.0	144	●	●
438	438.0	146	●	—
444	444.0	148	●	—
447	447.0	149	●	●
453	453.0	151	●	—
456	456.0	152	●	—
459	459.0	153	●	—
468	468.0	156	●	—
471	471.0	157	●	—
474	474.0	158	●	—
480	480.0	160	●	—
486	486.0	162	●	●
489	489.0	163	●	—
492	492.0	164	●	—
498	498.0	166	●	—
501	501.0	167	●	—
504	504.0	168	—	●
507	507.0	169	—	●
513	513.0	171	●	●
516	516.0	172	●	—
519	519.0	173	●	—
522	522.0	174	●	—
525	525.0	175	●	—
534	534.0	178	●	—
537	537.0	179	●	—
540	540.0	180	●	—
549	549.0	183	●	—
552	552.0	184	●	—
555	555.0	185	●	●
564	564.0	188	●	—
573	573.0	191	●	—
579	579.0	193	●	—
588	588.0	196	●	●
597	597.0	199	●	—
600	600.0	200	●	—
609	609.0	203	●	—
621	621.0	207	●	—
633	633.0	211	●	●
636	636.0	212	●	—
648	648.0	216	●	—
657	657.0	219	●	—
660	660.0	220	●	—
666	666.0	222	●	●
681	681.0	227	●	—
690	690.0	230	●	—
699	699.0	233	●	—
720	720.0	240	●	—
726	726.0	242	●	—
735	735.0	245	●	—
741	741.0	247	●	—
750	750.0	250	—	●
765	765.0	255	—	●
768	768.0	256	—	—
771	771.0	257	●	—
789	789.0	263	●	—
804	804.0	268	●	—
810	810.0	270	●	—
825	825.0	275	●	—
831	831.0	277	●	—
852	852.0	284	●	—
858	858.0	286	●	—
882	882.0	294	●	—
885	885.0	295	●	●
888	888.0	296	●	—
900	900.0	300	●	—
909	909.0	303	●	—
918	918.0	306	●	—
927	927.0	309	●	—
936	936.0	312	●	●
951	951.0	317	—	●
954	954.0	318	—	—
990	990.0	330	—	—
999	999.0	333	●	—
1005	1005.0	335	—	—
1014	1014.0	338	●	—
1050	1050.0	350	●	—
1119	1119.0	373	●	—
1134	1134.0	378	●	—
1146	1146.0	382	●	—
1176	1176.0	392	●	—
1188	1188.0	396	●	—
1260	1260.0	420	—	—
1299	1299.0	433	—	—
1383	1383.0	461	—	●
1419	1419.0	473	—	—
1530	1530.0	510	●	—
1587	1587.0	529	●	—
1596	1596.0	532	—	●
1800	1800.0	600	—	●
2100	2100.0	700	—	●