

S2M · DS2M형 기준 전동용량표 (4mm폭당)

단위 : W

소 풀 리 잇 수	34	36	40	44	48	50	60				
피치원직경 (mm)	21.65	22.92	25.46	28.01	30.56	31.83	38.2				
소 풀 리 회 전 수 (m p r)	725	31	32	36	39	42	44	51			
	870	35	37	41	45	49	50	59			
	950	38	40	44	48	52	54	63			
	1160	44	47	52	56	61	63	73			
	1425	52	55	60	66	71	73	86			
	1750	61	64	70	77	83	86	99			
	2850	86	91	100	109	117	121	140			
	3450	99	104	115	124	134	138	159			
	50	3	3	4	4	5	5	6			
	100	6	6	7	8	8	9	10			
	200	11	11	12	14	15	15	18			
	300	15	16	17	19	21	21	25			
	400	19	20	22	24	26	27	32			
	500	23	24	27	29	31	32	38			
	600	26	28	31	34	36	38	44			
	700	30	31	35	38	41	42	50			
	800	33	35	39	42	46	47	55			
	900	36	38	42	46	50	52	60			
	1000	39	42	46	50	54	56	66			
	1100	42	45	50	54	58	60	70			
소 풀 리 회 전 수 (m p r)	1200	45	48	53	58	62	65	75			
	1300	48	51	56	61	66	69	80			
	1400	51	54	60	65	70	73	84			
	1500	54	57	63	68	74	76	89			
	1600	57	60	66	72	77	80	93			
	1700	59	63	69	75	81	84	97			
	1800	62	65	72	78	84	87	102			
	1900	64	68	75	82	88	91	106			
	2000	67	71	78	85	91	94	110			
	2100	69	73	81	88	95	98	113			
소 풀 리 회 전 수 (m p r)	2200	72	76	83	91	98	101	117			
	2300	74	78	86	94	101	104	121			
	2400	76	81	89	97	104	108	125			
	2500	79	83	91	99	107	111	128			
	2600	81	85	94	102	110	114	132			
	2700	83	88	97	105	113	117	135			
	2800	85	90	99	108	116	120	139			
	2900	87	92	102	110	119	123	142			
	3000	90	95	104	113	122	126	145			
	3200	94	99	109	118	127	131	151			
소 풀 리 회 전 수 (m p r)	3400	98	103	114	123	132	137	158			
	3600	10	107	118	128	138	142	164			
	3800	106	111	122	133	143	147	169			
	4000	109	115	127	137	148	152	175			
	4200	113	119	134	142	152	157	180			
	4400	116	123	135	146	157	162	185			
	4600	120	126	139	150	161	167	190			
	4800	123	130	143	155	166	171	195			
	5000	127	133	147	159	170	175	200			
	5500	134	142	155	168	180	186	211			
소 풀 리 회 전 수 (m p r)	6000	142	150	164	177	189	195	221			
	6500	149	157	172	185	198	204	230			
	7000	156	164	179	193	206	212	238			
	7500										
	8000										
소 풀 리 회 전 수 (m p r)	8500										
	9000										