

S14M · DS14M형 기준 전동용량표 (120mm폭당)

단위 : kW

소 폴 리 잇 수		50	60	64	72	84	96	120	144
피치원직경 (mm)		222.82	267.38	285.21	320.86	374.33	427.81	534.76	641.71
소	575	56.88	67.97	72.36	81.06	93.87	106.37	130.21	152.23
	690	67.97	81.06	86.22	96.40	111.27	125.58	152.23	175.71
	725	71.31	84.99	90.38	100.98	116.42	131.21	158.51	182.13
	870	84.99	100.98	107.23	119.43	136.93	153.32	182.13	204.60
	950	92.41	109.57	116.25	129.22	147.62	164.58	193.33	213.82
	1160	111.34	131.21	138.81	153.32	173.17	190.39	215.43	225.43
	1425	133.94	156.29	164.58	179.88	199.29	213.82	225.46	209.22
	1750	159.24	182.87	191.12	205.25	219.88	225.47	204.39	
	2850	217.46	225.46	223.42	209.22	159.53			
	3450	225.37	207.49	191.03					
	20	2.00	2.40	2.56	2.88	3.36	3.84	4.79	5.75
	40	4.00	4.79	5.11	5.75	6.71	7.67	9.59	11.50
	60	5.99	7.19	7.67	8.63	10.07	11.50	14.38	17.25
	80	7.99	9.59	10.23	11.50	13.42	15.33	19.16	22.98
	100	9.99	11.98	12.78	14.38	16.77	19.16	23.93	28.70
	150	14.97	17.96	19.16	21.55	25.13	28.70	35.82	42.92
	200	19.95	23.93	25.52	28.70	33.45	38.19	47.63	56.98
	250	24.93	29.89	31.87	35.82	41.74	47.63	59.31	70.84
	300	29.89	35.82	38.19	42.92	49.97	56.98	70.84	84.43
	350	34.84	41.74	44.49	49.97	58.14	66.24	82.19	97.71
회	400	39.77	47.63	50.75	56.98	66.24	75.40	93.32	110.63
	450	44.69	53.48	56.98	63.94	74.26	84.43	104.22	123.13
	500	49.58	59.31	63.17	70.84	82.18	93.32	114.85	135.17
	600	59.31	70.84	75.40	84.43	97.71	110.63	135.17	157.62
	700	68.93	82.19	87.41	97.71	112.75	127.20	154.04	177.58
전	800	78.43	93.32	99.17	110.63	127.20	142.91	171.23	194.63
	900	87.78	104.22	110.63	123.14	140.99	157.63	186.50	208.34
	1000	96.99	114.85	121.77	135.17	154.04	171.23	199.59	218.31
	1100	106.01	125.17	132.54	146.68	166.27	183.61	210.28	224.12
수	1200	114.85	135.17	142.91	157.63	177.58	194.63	218.31	225.35
	1300	123.48	144.80	152.84	167.94	187.91	204.17	223.46	221.59
(m p r)	1400	131.88	154.04	162.29	177.58	197.16	212.10	225.47	212.41
	1500	140.03	162.86	171.24	186.50	205.25	218.31	224.12	197.41
	1600	147.93	171.23	179.63	194.63	212.10	222.67	219.15	
	1700	155.55	179.12	187.44	201.93	217.63	225.06	210.33	
	1800	162.87	186.50	194.63	208.34	221.76	225.35	197.41	
	1900	169.87	193.33	201.16	213.82	224.40	223.42		
	2000	176.55	199.59	207.00	218.31	225.47	219.15		
	2200	188.84	210.28	216.44	224.12	222.58	203.08		
	2400	199.59	218.31	222.67	225.35	212.41			
	2600	208.67	223.46	225.40	221.58	194.31			
리	2800	215.94	225.47	224.32	212.41				
	3000	221.26	224.12	219.15	197.40				
	3200	224.49	219.15	209.59					
	3400	225.49	210.33	195.36					
	3600	224.12	197.41						
	3800	220.24	180.15						
	4000	213.71							
	4500	184.88							
	5000								

표시범위에서의 사용은 벨트속도가 33m/s 이상이므로 폴리의 밸런스를 잡고 사용하여 주십시오.