

S2M · DS2M형 허용장력표 (4mm폭당)

단위 : N

소 폴 리 잇 수	34	36	40	44	48	50	60				
피치원직경 (mm)	21.65	22.92	25.46	28.01	30.56	31.83	38.20				
소 폴 리 회 전 수 (m p r)	725	37	37	37	37	36	36	35			
	870	36	36	36	35	35	35	34			
	950	35	35	35	35	34	34	33			
	1160	34	34	33	33	33	33	32			
	1425	32	32	32	31	31	31	30			
	1750	31	30	30	30	30	29	28			
	2850	27	27	26	26	26	26	25			
	3450	25	25	25	25	24	24	25			
	50	58	58	57	57	57	57	56			
	100	52	52	52	52	52	51	50			
	200	47	47	47	47	46	46	45			
	300	44	44	44	43	43	43	42			
	400	42	42	42	41	41	41	40			
	500	40	40	40	40	39	39	38			
	600	39	39	39	38	38	38	37			
	700	38	37	37	37	37	36	36			
	800	37	36	36	36	36	35	34			
	900	36	36	35	35	35	34	34			
	1000	35	35	35	34	34	34	33			
	1100	34	34	34	33	33	33	32			
소 폴 리 회 전 수 (m p r)	1200	33	33	33	33	32	32	31			
	1300	33	33	33	32	32	32	31			
	1400	32	32	32	32	31	31	30			
	1500	32	32	31	31	31	31	30			
	1600	31	31	31	31	30	30	29			
	1700	31	31	30	30	30	30	29			
	1800	30	30	30	30	29	29	28			
	1900	30	30	30	29	29	29	28			
	2000	30	30	29	29	29	29	27			
	2100	29	29	29	29	28	28	27			
	2200	29	29	28	28	28	28	27			
	2300	28	28	28	28	27	27	26			
	2400	28	28	28	27	27	27	26			
	2500	28	28	27	27	27	27	26			
	2600	27	27	27	27	27	26	25			
	2700	27	27	27	27	26	26	25			
	2800	27	27	27	26	26	26	25			
	2900	27	27	26	26	26	26	25			
	3000	26	26	26	26	25	25	24			
	3200	26	26	26	25	25	25	24			
소 폴 리 회 전 수 (m p r)	3400	25	25	25	25	24	24	23			
	3600	25	25	25	24	24	24	23			
	3800	25	25	24	24	24	23	23			
	4000	24	24	24	24	23	23	22			
	4200	24	24	24	23	23	23	22			
	4400	23	23	23	23	23	23	21			
	4600	23	23	23	23	22	22	21			
	4800	23	23	22	22	22	22	21			
	5000	22	22	22	22	22	21	20			
	5500	22	22	21	28	21	21	20			
	6000	21	21	21	20	20	20	19			
	6500	20	20	20	20	20	19	18			
	7000	20	20	20	19	19	19	18			
	7500										
	8000										
	8500										
	9000										